

TAURUS MULTIBATTERY LED

DETAILED CARD



TECHNICAL PARAMETERS

Index:	256882
Ingress protection:	IP65
Impact resistance:	IK08
Colour temperature [K] - range:	2700 - 6500
Luminous flux [lm]*:	5000
Supply voltage [V]:	18
Electrical protection class:	III
Material of the body:	PP
Colour of the body:	green
Diffuser type:	milky

CHARACTERISTICS

Compact LED floodlight for professional use. Provides even and stable directional illumination. Made from impact-resistant polypropylene (PP). Smaller size and compact design make it more convenient to transport. Equipped with an on/off switch with 4-stage luminous flux adjustment. An additional button allows adjustment of the light colour in the range: 2700K to 6500K. The lamp is compatible with 18V batteries from manufacturers such as Bosch (18V Professional), Milwaukee, DeWalt, Metabo. The unit has a display showing the battery charge level.

Operating modes for battery operation:

- for 5Ah Battery:
- 500 lm - operating time: 20h
 - 1850 lm - operating time: 7h 15min
 - 2750 lm - operating time: 4h 30min
 - 4050 lm - operating time: 2h 15min

APPLICATION

It can be used as a workplace luminaire to illuminate workplaces, workshops or garages.

TAURUS MULTIBATTERY LED

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	256882	Ingress protection:	IP65
Light source:	LED module	Net weight [kg]:	2.770
Luminous flux [lm]:	5000	Category type:	workplace floodlights
Colour temperature [K] - range:	2700 - 6500	LED lifespan L70B50 [h]:	140000
Supply voltage [V]:	18	LED lifespan L80B20 [h]:	85000
Electrical protection class:	III	LED lifespan L90B10 [h]:	42000
Colour rendering index:	>80	Light distribution type:	lamertian
SDCM:	≤ 3	Additional accessories:	Adapter for Bosch 18V. Milwaukee 18V, DeWalt 18V, Makita 18V and Metabo 18V batteries.
Beam angle [°]:	120	ETIM class:	EC000346
Diffuser type:	milky	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	PP	Warranty [years]:	2
Colour of the body:	green	CE certificate:	77/2024
Dimensions (H/W/T/S) [mm]:	280/280/148	Manual:	Download PDF
Impact resistance:	IK08		